

ZHEJIANG KAIFENG NEW MATERIAL LIMITED BY SHARE LTD
Wrapping Paper / Bleached Kraft Paper / Waxed Base Paper

Material				Application											
Bleached Kraft Paper is made primarily from high-quality bleached softwood kraft pulp. Formed on a fourdrinier machine and finished by high-pressure calendering, it provides excellent strength, smoothness, and reliable performance for food and general packaging applications.				Suitable for food packaging and paper bags for bakery products, fast food, tea, nuts, and other food applications.											
TDS No:		KFJS-SPBZ0205D		Testing Condition: 23±1 °C & 50±3 % Date: January 2025											
Item			Unit	Standard		Tolerance			Nominal						
1. Grammage			g/m ²	ISO 536	±5%	22	23	25	28	30	33	35	40		
2. Moisture			%	ISO 287	±2	6									
3. Thickness			µm	ISO 534	±5	29	31	33	37	40	44	47	53		
4. Cobb	US		g/m ²	ISO 535	≤	25									
5. Tensile strength	MD		N/15mm	ISO 1924-2	≥	18	19	22	25	27	30	32	36		
	CD					9	10	11	12	13	15	16	18		
6. Opacity			%	ISO2471	≥	60									
7. D65 brightness			%	GB/T 24999	≥	86									
8. Smoothness (US)			S	ISO 5627	≥	300									
9. OBA			/	GB31604.47	/	negative									
10. Odour			/	EN 1230	/	≤ level 1									
11. Dust degree	0.2mm ² -1.0mm ²		pcs/m ²	GB/T 1541	≤	20									
	> 1.0mm ²					none									
MD = Machine Direction CD = Cross Direction															
This product complies with the standards of GB4806.8, US FDA 21, CFR 176170, ECNo1935/2004 and BfR XXXV.															
Core general requirements: inner diameter is 76mm.															
These values are average values from the production results and do never form a specification for a certain product.															
The above date does not relieve the user from carrying out tests by himself.															
A legal binding assurance of specific properties for a specific application purpose cannot be given.															